

HONEYWELL Fire Systems

Remote Indicator LED's

General

Honeywell supply a range of remote indicators for use with both conventional and addressable fire alarm systems in most applications.

Versions

- In Concealed Space
- In Duct
- In Roof
- Inside Room
- Under Floor
- In Lift Shaft

Features

- Low current consumption
- Three terminal design with resistive and non resistive terminals
- Suits System Sensor and other brands
- Easy to install
- Pre drilled counter sunk holes



Specifications:

Current: 15ma max
Brightness: 9 mcd
Voltage: 15VDC to 24vdc
Terminals: (Common D -)
(Resistive R+)
(Non resistive D+)

Connections:

Type Detector Base

System Sensor Conventional Base B401
System Sensor Conventional Base B401R
System Sensor Addressable Base B501
Hochiki Conventional Base YBO-R/4A

Remote indicator

Terminals 1+ and 2 - D - and R+
Terminals 1+ and 2 - D - and D+
Terminals 3+ and 1 - D - and R+
Terminals 3+ and 6 - D - and D+

This document is not intended for installation purposes.
Honeywell Security try to keep our product information up-to-date and accurate.
We cannot cover all specific applications or anticipate all requirements.
All specifications are subject to change without notice

For more information contact your nearest Honeywell Branch
www.honeywellsecurity.com.au